

SERVICE SPECIFICATIONS

MA010-01

SERVICE DATA

Drive belt tension			
Alternator		New belt	120 ± 20 lbf
Alternator		Used belt	104 ± 20 lbf
A/C compressor		New belt	160 ± 25 lbf
A/C compressor		Used belt	100 ± 20 lbf
Spark plug	Recommended spark plug	ND	PK20R8
Spark plug	Recommended spark plug	NGK	BKR6EP8
Spark plug	Correct electrode gap		0.8 mm (0.0031 in.)
Firing order			1 - 3 - 4 - 2
Valve clearance		Intake	0.15 - 0.25 mm (0.006 - 0.010 in.)
Valve clearance		Exhaust	0.28 - 0.38 mm (0.011 - 0.015 in.)
Front and rear brake			
Pad thickness		Minimum	1.0 mm (0.039 in.)
Disc thickness	Front	Minimum	28.0 mm (1.102 in.)
Disc thickness	Rear	Minimum	21.0 mm (0.827 in.)
Disc runout	Front	Maximum	0.07 mm (0.0028 in.)
Disc runout	Rear	Maximum	0.10 mm (0.0039 in.)
Front axle and suspension			
Ball joint vertical play		Maximum	0 mm (0 in.)
Steering wheel freeplay		Maximum	30 mm (1.18 in.)

TORQUE SPECIFICATIONS

MA000-02

Pert tightened	N-m	kgf-cm	ft-lbf
Seat mounting bolts	37	375	27
Strut bar bracket-to-body mounting bolts	80	820	59
Rear suspension lower crossmember-to-body mounting bolts	113	1,150	83