

# SERVICE SPECIFICATIONS

MA002-08

## SERVICE DATA

Drive belt tension			
Alternator		New belt	<b>120 ± 20 lbf</b>
Alternator		Used belt	<b>104 ± 20 lbf</b>
A/C compressor		New belt	<b>160 ± 25 lbf</b>
A/C compressor		Used belt	<b>100 ± 20 lbf</b>
Spark plug	Recommended spark plug	ND	<b>PK20R11</b>
Spark plug	Recommended spark plug	NGK	<b>BKR6EP-11</b>
Spark plug	Correct electrode gap		<b>1.1 mm (0.0043 in.)</b>
Firing order			<b>1 - 3 - 4 - 2</b>
Valve clearance		Intake	<b>0.19 - 0.29 mm (0.007 - 0.011 in.)</b>
Valve clearance		Exhaust	<b>0.28 - 0.38 mm (0.011 - 0.015 in.)</b>
Front and rear brake			
Pad thickness		Minimum	<b>1.0 mm (0.039 in.)</b>
Disc thickness	Front	Minimum	<b>24.0 mm (0.787 in.)</b>
Disc thickness	Rear	Minimum	<b>15.0 mm (0.590 in.)</b>
Disc runout	Front	Maximum	<b>0.07 mm (0.0028 in.)</b>
Disc runout	Rear	Maximum	<b>0.10 mm (0.0039 in.)</b>
Front axle and suspension			
Bell joint vertical play		Maximum	<b>0 mm (0 in.)</b>
Steering wheel freeplay		Maximum	<b>30 mm (1.18 in.)</b>

## TORQUE SPECIFICATIONS

MA000-03

Part tightened	N-m	kgf-cm	ft-lbf
Seat mounting bolts	<b>37</b>	<b>375</b>	<b>27</b>
Strut bar bracket-to-body mounting bolts	<b>80</b>	<b>820</b>	<b>59</b>
Rear suspension lower crossmember-to-body mounting bolts	<b>113</b>	<b>1,150</b>	<b>83</b>