

SERVICE SPECIFICATIONS

1001P-02

SERVICE DATA

Ignition timing	w/ Terminals TE1 and E1 connected	10° BTDC @ idle
Firing order	-	1 - 3 - 4 - 2
High-tension cord	Resistance (Maximum)	25 kΩ per cord
Spark plug	Recommended spark plug ND	PK20R8
	Recommended spark plug NGK	BKR6EP8
	Correct electrode gap	0.8 mm (0.031 in.)
	Maximum electrode gap of used plug	1.0 mm (0.039 in.)
Ignition coil	Primary coil resistance (Cold)	0.36 - 0.55 Ω
	Primary coil resistance (Hot)	0.45 - 0.65 Ω
	Secondary coil resistance (Cold)	9.0 - 15.4 kΩ
	Secondary coil resistance (Hot)	11.4 - 18.1 kΩ
Distributor	Air gap	0.2 - 0.5 mm (0.008 - 0.020 in.)
	Signal generator (pickup coil) resistance (Cold)	
	G1 - G(-)	125 - 200 Ω
	G2 - G(-)	125 - 200 Ω
	NE - G(-)	155 - 250 Ω
	Signal generator (pickup coil) resistance (Hot)	
	G1 - G(-)	160 - 235 Ω
	G2 - G(-)	160 - 235 Ω
NE - G(-)	195 - 290 Ω	

TORQUE SPECIFICATIONS

1001Q-02

Part tightened	N-m	kgf-cm	ft-lbf
Spark plug x Cylinder head	18	180	13
Distributor x Cylinder head	39	400	29